



**CIVIL AVIATION RULES AND STANDARDS**  
**FEDERAL DEMOCRATIC REPUBLIC OF ETHIOPIA**  
**PART 20**  
**UNITS OF MEASUREMENT**  
**TO BE USED IN AIR AND GROUND OPERATIONS**

**March 2015**



**TABLE OF CONTENTS**

AMENDMENTS ..... ii

TABLE OF CONTENTS ..... iii

FOREWORD ..... 1

1. DEFINITIONS..... 2

    2. Applicability..... 5

3. Standard Application of Units of Measurement ..... 5

4 Termination of use of Non-SI Alternative units..... 12

ATTACHMENT 20A ..... 14

DEVELOPMENT OF THE INTERNATIONAL SYSTEM OF UNITS (SI) ..... 14

    1 Historical Background ..... 14

    2. International Bureau of Weights and Measures ..... 15

ATTACHMENT 20 B..... 20

GUIDANCE ON THE APPLICATION OF THE SI..... 20

    1. Introduction..... 20

    2. Mass, force and weight ..... 23

    3. Energy and torque ..... 24

    4. SI prefixes..... 25

    5. Style and usage ..... 26

ATTACHMENT 20C..... 30

CONVERSION FACTORS ..... 30

    1. General..... 30

    2. Factors not listed..... 31

ATTACHMENT 20D..... 43

CO-ORDINATED UNIVERSAL TIME..... 43

ATTACHMENT 20 E..... 45

PRESENTATION OF DATE AND TIME IN ALL-NUMERIC FORM..... 45

    1. Introduction..... 45

    2. Presentation of Date ..... 45

    3. Presentation of Time ..... 46

    4 Combination of Date and Time Groups ..... 46

### **FOREWORD**

This Civil Aviation Rules and Standards-part 20 was formulated and issued by the Ethiopia Civil Aviation Authority (ECAA), prescribing the standards and recommended practices for units of measurements to be used in air and ground operations within Addis Ababa Flight Information Region. This Civil Aviation Rules and Standards-part 20 was developed based on the Standards and Recommended Practices prescribed by the International Civil Aviation Organization (ICAO) as contained in Annex 5. The provisions contained herein are issued by authority of the Director General of Ethiopian Civil Aviation Authority and will be complied with by all concerned.

Amendments will be issued from time to time and distributed to all concerned units as case may be, following ICAO amendments to the SARPS in Annex- 5 or when a requirement arises locally for Inclusion of additional requirements.

Any query relating to this document should be addressed to:-

The Ethiopian Civil Aviation Authority

#### **Air Navigation Department**

P.O. Box 978

Addis Ababa Ethiopia

Fax 251 11 612533

Tel. 251-11-6650226

E-mail [caa.airnav@Ethionet.et](mailto:caa.airnav@Ethionet.et).

## 1. DEFINITIONS

### 1.1 Definition of Terms

In this regulation the terms listed below have the following meanings whenever they appear:

**Ampere (A)** - The ampere is that constant electric current which, if maintained in two straight parallel conductors of infinite length, of negligible circular cross-section, and placed 1 Meter apart in vacuum, would produce between these conductors a force equal to  $2 \times 10^{-7}$  Newton per Meter of length.

**Becquerel (Bq)** - The activity of a radionuclide having one spontaneous nuclear transition per second.

**Candela (cd)** - The luminous intensity, in the perpendicular direction, of a surface of  $1/600000$  square Meter of black body at the temperature of freezing platinum under a pressure of 101325 newtons per square Meter.

**Celsius temperature (toC)** - The Celsius temperature is equal to the difference  $T - T_0$  between two thermodynamic temperatures  $T$  and  $T_0$  where  $T_0$  equals 273.15 Kelvin.

**Coulomb (C)** - The quantity of electricity transported in 1 second by a current of 1 ampere.

**Degree Celsius (oC)** - The special name for the unit Kelvin for use in stating values of Celsius temperature.

**Farad (F)** - The capacitance of a capacitor between the plates of which there appears a difference of potential of 1 volt when it is charged by a quantity of electricity equal to 1 coulomb.

**Foot (ft)** - The length equal to 0.3048 Meter exactly.

**Gray (Gy)** - The energy imparted by ionizing radiation to a mass of matter corresponding to 1 joule per kilogram.

**Henry (H)** - The inductance of a closed circuit in which an electromotive force of 1 volt is produced when the electric current in the circuit varies uniformly at a rate of 1 ampere per second.

**Hertz (Hz)** - The frequency of a periodic phenomenon of which the period is 1 second.

**Human performance** - Human capabilities and limitations which have an impact on the safety and efficiency of aeronautical operations.

**Joule (J)** - The work done when the point of application of a force of 1 Newton is displaced a distance of 1 Meter in the direction of the force.

**Kelvin (K)** - A unit of thermodynamic temperature which is the fraction of  $1/273.16$  of the thermodynamic temperature of the triple point of water.

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

**Kilogram (kg)** – The unit of mass equal to the mass of the international prototype of the kilogram.

**Knot (kt)** – The speed equal to 1 nautical mile per hour.

**Litre (L)** – A unit of volume restricted to the measurement of liquids and gases which is equal to 1 cubic decimeter.

**Lumen (lm)** – The luminous flux emitted in a solid angle of 1 steradian by a point source having a uniform intensity of 1 candela.

**Lux (lx)** – The illuminance produced by a luminous flux of 1 lumen uniformly distributed over a surface of 1 square metre.

**Metre (m)** – The distance traveled by light in a vacuum during  $1/299792458$  of a second.

**Mole (mol)** – The amount of substance of a system which contains as many elementary entities as there are atoms in 0.012 kilogram of carbon-12.

Note : When the mole is used, the elementary entities must be specified and may be atoms, molecules, ions, electrons, other particles or specified groups of such particles.

**Nautical Mile (NM)** – The length equal to 1852 metres exactly.

**Newton (N)** – The force which when applied to a body having a mass of 1 kilogram gives it an acceleration of 1 metre per second squared.

**Ohm ( $\Omega$ )** – The electric resistance between two points of a conductor when a constant difference of potential of 1 volt, applied between these two points, produces in this conductor a current of 1 ampere, this conductor not being the source of any electromotive force.

**Pascal (Pa)** – The pressure or stress of 1 newton per square metre.

**Radian (rad)** – The plane angle between two radii of a circle which cut off on the circumference an arc equal in length to the radius.

**Second (s)** – The duration of 9192631770 periods of the radiation corresponding to the transition between the two hyperfine levels of the ground state of the caesium-133 atom.

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

**Siemens (S)** – The electric conductance of a conductor in which a current of 1 ampere is produced by an electric potential difference of 1 volt.

**Sievert (Sv)** – The unit of radiation dose equivalent corresponding to 1 joule per kilogram.

**Steradian (sr)** – The solid angle which, having its vertex in the centre of a sphere, cuts off an area of the surface of the sphere equal to that of a square with sides of length equal to the radius of the sphere.

**Tesla (T)** – The magnetic flux density given by a magnetic flux of 1 weber per square metre.

**Tonne (t)** – The mass equal to 1000 kilograms.

**Volt (V)** – The unit of electric potential difference and electromotive force which is the difference of electric potential between two points of a conductor carrying a constant current of 1 ampere, when the power dissipated between these points is equal to 1 watt.

**Watt (W)** – The power which gives rise to the production of energy at the rate of 1 joule per second.

**Weber (Wb)** – The magnetic flux which, linking a circuit of one turn, produces in it an electromotive force of 1 volt as it is reduced to zero at a uniform rate in 1 second.

## **2. Applicability**

Civil Aviation Rules and Standards part 20 specifies for the use of a standardized system of units of measurement in Ethiopian Civil Aviation air and ground operations. This standardized system of units of measurement is based on the International System of Units (SI) and certain non-SI units considered necessary to meet the specialized requirements of International Civil Aviation. The provision of this Rules and Standards shall be applicable to all aspects of civil aviation air and ground operations.

## **3. Standard Application of Units of Measurement**

### **3.1. Use of the SI Units as the standard system of units of measurements**

3.1.1 The International System of Units developed and maintained by the General Conference of Weights and Measures (CGPM) shall, subject to the provisions of 3.2 and 3.3, be used as the standard system of units of measurements for Ethiopian Civil Aviation air and ground operations.

3.1.2. The prefixes and symbols listed in the table below shall be used to form names and symbols of the decimal multiples and sub-multiples of SI units.

<i><b>Multiplication factor</b></i>	<i><b>Prefix</b></i>	<i><b>Symbol</b></i>
1 000 000 000 000 000 000 = 10 <sup>18</sup>	exa	E
1 000 000 000 000 000 = 10 <sup>15</sup>	peta	P
1 000 000 000 000 = 10 <sup>12</sup>	tera	T
1 000 000 000 = 10 <sup>9</sup>	giga	G
1 000 000 = 10 <sup>6</sup>	mega	M
1 000 = 10 <sup>3</sup>	kilo	k
100 = 10 <sup>2</sup>	hecto	h

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

10 = 10 <sup>1</sup>	deca	da
0.1 = 10 <sup>-1</sup>	deci	d
0.01 = 10 <sup>-2</sup>	centi	c
0.001 = 10 <sup>-3</sup>	milli	m
0.000 001 = 10 <sup>-6</sup>	micro	μ
0.000 000 001 = 10 <sup>-9</sup>	nano	n
0.000 000 000 001 = 10 <sup>-12</sup>	pico	p
0.000 000 000 000 001 = 10 <sup>-15</sup>	femto	f
0.000 000 000 000 000 001 = 10 <sup>-18</sup>	atto	a

### 3.2 Use of the Non-SI Units for permanent use with the SI Units

3.2.1 the non-SI units listed in Table 1 shall be used either in lieu of, or in addition to, SI units as primary units of measurement but only specified in Table 3.

Table 1: Non-SI units for use with the SI

<i>Specific quantities in Table 3 related to</i>	<i>Unit</i>	<i>Symbol</i>	<i>Definition (in terms of SI units)</i>
<i>Mass</i>	<i>Tonne</i>	<i>t</i>	<i>1 t = 10<sup>3</sup> kg.</i>
<i>plane angle</i>	<i>degree minute second</i>	<i>° ' "</i>	<i>1° = (π/180)rad 1' = (1/160)° = (π/10 800) rad 1" = (1/160)' = (π/648 000) rad</i>
<i>temperature</i>	<i>degree Celsius</i>	<i>°C</i>	<i>1 unit °C = 1 unit Ka)</i>
<i>time</i>	<i>minute hour day week, month, year</i>	<i>min h d -</i>	<i>1 min = 60 s 1 h = 60 min = 3 600s 1 d = 24 h = 86 400 s</i>
<i>volume</i>	<i>litre</i>	<i>L</i>	<i>1 L = 1 dm<sup>3</sup> = 10<sup>-3</sup> m<sup>3</sup></i>
<i>a) See Attachment C, Table C-2 for conversion.</i>			

3.2.2 The non-SI units listed in Table 2 shall be permitted for temporary use as alternative units of measurement but only for those specific quantities listed in Table 3.

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

Table 2: Non-SI alternative units permitted for temporary use with the SI

<i>Specific quantities in Table 3 related to</i>	<i>Unit</i>	<i>Symbol</i>	<i>Definition (in terms of SI units)</i>
<i>distance (long)</i>	<i>nautical mile</i>	<i>NM</i>	<i>1 NM = 1 852 m</i>
<i>distance (vertical)<sup>a)</sup></i>	<i>foot</i>	<i>ft</i>	<i>1 ft = 0.304 8 m</i>
<i>speed</i>	<i>knot</i>	<i>kt</i>	<i>1 kt = 0.514 444 m/s</i>
<i>a) altitude, elevation, height, vertical speed.</i>			

### 3.3 The application of units of measurement for certain quantities

3.3.1 The application of units of measurement for certain quantities used in Ethiopia civil aviation air and ground operations shall be in accordance in Table 3 which is listed below:

<i>Ref. No.</i>	<i>Quantity</i>	<i>Primary unit(symbol)</i>	<i>Non-SI Alternative Unit (symbol)</i>
<i>1. Direction/ Space/ Time</i>			
<i>1.1</i>	<i>altitude</i>	<i>m</i>	<i>ft</i>
<i>1.2</i>	<i>area</i>	<i>m<sup>2</sup></i>	
<i>1.3</i>	<i>distance (long)<sup>a)</sup></i>	<i>km</i>	<i>NM</i>
<i>1.4</i>	<i>distance (short)</i>	<i>m</i>	
<i>1.5</i>	<i>elevation</i>	<i>m</i>	<i>ft</i>
<i>1.6</i>	<i>endurance</i>	<i>h and min</i>	
<i>1.7</i>	<i>height</i>	<i>m</i>	<i>ft</i>
<i>1.8</i>	<i>latitude</i>	<i>0 ‘ ‘</i>	
<i>1.9</i>	<i>length</i>	<i>m</i>	
<i>1.10</i>	<i>longitude</i>	<i>0 ‘ ‘</i>	
<i>1.11</i>	<i>plane angle (when required,</i>	<i>0</i>	

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

	<i>decimal subdivisions of the degree shall be used)</i>		
1.12	<i>runway length</i>	<i>m</i>	
1.13	<i>runway visual range</i>	<i>m</i>	
1.14	<i>tank capacities (aircraft)<sup>b)</sup></i>	<i>L</i>	
1.15	<i>time</i>	<i>s min h d week month year</i>	
1.16	<i>visibility <sup>c)</sup></i>	<i>km</i>	
1.17	<i>volume</i>	<i>m<sup>3</sup></i>	
1.18	<i>other than for a landing and take-off shall be expressed in degrees true; for landing and take-off wind directions shall be expressed in degrees magnetic)</i>	<i>0</i>	
<b>2. Mass-related</b>			
2.1	<i>air density</i>	<i>kg/m<sup>3</sup></i>	
2.2	<i>area density</i>	<i>kg/m<sup>2</sup></i>	
2.3	<i>cargo capacity</i>	<i>kg</i>	
2.4	<i>cargo density</i>	<i>kg/m<sup>3</sup></i>	
2.5	<i>density (mass density)</i>	<i>kg/m<sup>3</sup></i>	
2.6	<i>fuel capacity (gravimetric)</i>	<i>kg</i>	
2.7	<i>gas density</i>	<i>kg/m<sup>3</sup></i>	
2.8	<i>gross mass or payload</i>	<i>kg t</i>	
2.9	<i>hoisting provisions</i>	<i>kg</i>	
2.10	<i>linear density</i>	<i>kg/m</i>	
2.11	<i>liquid density</i>	<i>kg/m<sup>3</sup></i>	
2.12	<i>mass</i>	<i>kg</i>	
2.13	<i>moment of inertia</i>	<i>Kg.m<sup>2</sup></i>	
2.14	<i>moment of momentum</i>	<i>Kg.m<sup>2</sup>/s</i>	

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

2.15	<i>momentum</i>	<i>Kg.m/s</i>	
<b>3. Force-related</b>			
3.1	<i>air pressure (general)</i>	<i>kPa</i>	
3.2	<i>altimeter setting</i>	<i>hPa</i>	
3.3	<i>atmospheric pressure</i>	<i>hPa</i>	
3.4	<i>bending moment</i>	<i>kN.m</i>	
3.5	<i>force</i>	<i>N</i>	
3.6	<i>fuel supply pressure</i>	<i>kPa</i>	
3.7	<i>hydraulic pressure</i>	<i>kPa</i>	
3.8	<i>modulus of elasticity</i>	<i>MPa</i>	
3.9	<i>pressure</i>	<i>kPa</i>	
3.10	<i>stress</i>	<i>MPa</i>	
3.11	<i>surface tension</i>	<i>mN/m</i>	
3.12	<i>thrust</i>	<i>kN</i>	
3.13	<i>torque</i>	<i>N -m</i>	
3.14	<i>vacuum</i>	<i>Pa</i>	
<b>4. Mechanics</b>			
4.1	<i>airspeed<sub>d</sub></i>	<i>km/h</i>	<i>kt</i>
4.2	<i>angular acceleration</i>	<i>rad/s<sup>2</sup></i>	
4.3	<i>angular velocity</i>	<i>rad/s</i>	
4.4	<i>energy of work</i>	<i>J</i>	
4.5	<i>equivalent shaft power</i>	<i>kW</i>	
4.6	<i>frequency</i>	<i>Hz</i>	
4.7	<i>ground speed</i>	<i>km/h</i>	<i>kt</i>
4.8	<i>impact</i>	<i>J/m<sup>2</sup></i>	
4.9	<i>kinetic energy absorbed by brakes</i>	<i>J/m</i>	
4.10	<i>linear acceleration</i>	<i>m/s<sup>2</sup></i>	
4.11	<i>power</i>	<i>kW</i>	
4.12	<i>rate of trim <math>\theta</math></i>	<i>0/s</i>	

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

4.13	shaft power	kW	
4.14	velocity	m/s	
4.15	vertical speed	m/s	ft/min
4.16	wind speed	km/h	kt
<b>5. Flow</b>			
5.1	Engine airflow	kg/s	
5.2	Engine waterflow	kg/h	
5.3	Fuel consumption (specific) Piston engines Turbo-shaft engines Jet engines	Kg.(kW-h) Kg.(kW-h) Kg.(kN-h)	
5.4	Fuel flow	kg/h	
5.5	Fuel tank filling rate (gravimetric)	kg/min	
5.6	Gas flow	kg/s	
5.7	Liquid flow (gravimetric)	g/s	
5.8	Liquid flow (volumetric)	L/s	
5.9	Mass flow	kg/s	
5.10	Oil consumption Gas turbine	Kg.h	
5.11	Oil flow	g.s	
5.12	Pump capacity	L/min	
5.13	Ventilation airflow	m <sup>3</sup> /min	
5.14	Viscosity (dynamic)	Pa.s	
5.15	Viscosity (kinematic)	m <sup>2</sup> .s	
<b>6. Thermodynamics</b>			
6.1	coefficient of heat transfer	W.(m <sup>2</sup> K)	
6.2	heat flow per unit area	J/m <sup>2</sup>	
6.3	heat flow rate	W	
6.4	humidity (absolute)	g/kg	
6.5	coefficient of linear expansion	°C <sup>-1</sup>	
6.6	quantity of heat	J	
6.7	temperature	°C	

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

<b>7. Electricity and magnetism</b>			
7.1	<i>capacitance</i>	<i>F</i>	
7.2	<i>conductance</i>	<i>S</i>	
7.3	<i>conductivity</i>	<i>S/m</i>	
7.4	<i>current density</i>	<i>A/m<sup>2</sup></i>	
7.5	<i>electric current</i>	<i>A</i>	
7.6	<i>electric field strength</i>	<i>C/m<sup>2</sup></i>	
7.7	<i>electric potential</i>	<i>V</i>	
7.8	<i>electromotive force</i>	<i>V</i>	
7.9	<i>magnetic field strength</i>	<i>A/m</i>	
7.10	<i>magnetic flux</i>	<i>Wb</i>	
7.11	<i>magnetic flux density</i>	<i>T</i>	
7.12	<i>power</i>	<i>W</i>	
7.13	<i>quantity of electricity</i>	<i>C</i>	
7.14	<i>resistance</i>	<i>Ω</i>	
<b>8. Light and related electromagnetic relations</b>			
8.1	<i>illuminance</i>	<i>lx</i>	
8.2	<i>luminance</i>	<i>cd/m<sup>2</sup></i>	
8.3	<i>luminous exitance</i>	<i>lm/m<sup>2</sup></i>	
8.4	<i>luminous flux</i>	<i>lm</i>	
8.5	<i>luminous intensity</i>	<i>cd</i>	
8.6	<i>quantity of light</i>	<i>lm.s</i>	
8.7	<i>radiant energy</i>	<i>J</i>	
8.8	<i>wavelength</i>	<i>m</i>	
<b>9. Acoustics</b>			
9.1	<i>frequency</i>	<i>Hz</i>	
9.2	<i>mass density</i>	<i>kg/m<sup>3</sup></i>	
9.3	<i>noise level</i>	<i>dB<sup>(e)</sup></i>	
9.4	<i>period periodic time</i>	<i>s</i>	

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

9.5	<i>sound intensity</i>	$W/m^2$	
9.6	<i>sound power</i>	$W$	
9.7	<i>sound pressure</i>	$Pa$	
9.8	<i>sound level</i>	$dB$ <sup>f)</sup>	
9.9	<i>static pressure (instantaneous)</i>	$Pa$	
9.10	<i>velocity of sound</i>	$m/s$	
9.11	<i>volume of velocity (instantaneous)</i>	$m^3/s$	
9.12	<i>wavelength</i>	$m$	
<b>10. Nuclear physics and ionizing radiation</b>			
10.1	<i>Absorbed dose</i>	$Gy$	
10.2	<i>Absorbed dose rate</i>	$Gy/s$	
10.3	<i>Activity of radionuclides</i>	$Bq$	
10.4	<i>Dose equivalent Sv</i>	<i>Dose equivalent Sv</i>	
10.5	<i>Radiation exposure</i>	$C/kg$	
10.6	<i>Exposure rate</i>	$C/kg s$	
<p>a) As used in navigation, generally in excess of 4 000 m.</p> <p>b) Such as aircraft fuel, hydraulic fluids, water, oil and high pressure oxygen vessels.</p> <p>c) Visibility of less than 5 km may be given in m.</p> <p>d) Airspeed is sometimes reported in flight operations in terms of the ratio MACH number.</p> <p>e) The decibel (dB) is a ratio which may be used as a unit for expressing sound pressure level and sound power level. When used, the reference level must be specified.</p>			

### 4 Termination of use of Non-SI Alternative units

#### 4.1 Termination of use of Non-SI Alternative units

4.1.1 The non-SI units listed in Table 2 have been retained temporarily for use as alternative units because of their wide-spread use and to avoid potential safety problems which could result from lack of international coordination concerning the termination of their use. The use in Ethiopian civil aviation

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

operations of the alternative non-SI units listed in Table 2 shall be terminated on the dates listed in the table below.

*Table 4 : Termination dates for non-SI alternative units*

<i>Non-SI alternative unit</i>	<i>Termination date</i>
<i>Knot } Nautical mile }</i>	<i>not established <sup>a)</sup></i>
<i>Foot</i>	<i>not established <sup>b)</sup></i>
<i>a) No termination date has yet been established for use of nautical mile and knot.</i>	
<i>b) No termination date has yet been established for use of the foot.</i>	

**ATTACHMENT 20A**

**DEVELOPMENT OF THE INTERNATIONAL SYSTEM OF UNITS (SI)**

**1 Historical Background**

- 1.1. The name SI is derived from “System International d’ Unities”. The system has evolved from the units of length and mass (metre and kilogram) created by the members of the Paris Academy of Sciences and adopted by the French National Assembly in 1795 as a practical measure to benefit industry and commerce. The original system became known as the metric system. Physicist realized the advantages of the system and it was soon adopted in scientific and technical circles.
- 1.2. International standardization began with the 1870 meeting of 15 states in Paris that led to International Metric Convention in 1875 and the establishment of a permanent International Bureau of Weight and Measures. A General Conference on Weights and Measures (CGPM) was constituted to handle all international matters concerning the metric system. In 1889 the first CGPM meeting legalized the old prototype of the metre and the kilogram as the international standard for unit of length and unit of mass respectively. Other units were agreed in subsequent meetings and by its 10th Meeting in 1954, the CGPM had adopted a rationalized and coherent system of units based on the metre-kilogramsecond- ampere (MKSA) system developed earlier, plus the addition of the Kelvin as the unit of temperature and the candela as the unit of luminous intensity. The 11th CGPM, held in 1960 in participated by 36 States, adopted the name International System of Units (SI) and laid down rules of prefixes, the derived and supplementary units and other matters, thus establishing comprehensive specifications for international units of measurements. The 12th CGPM in 1964 made some refinements in the system, and the 13th CGPM in 1967 redefined the second, renamed the units of temperature as the Kelvin (K) and revised the definition of the candela. The 14th CGPM in 1971 added a seventh base unit, the mole (mol) and approved

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

the pascal (Pa) as a special name for the SI unit of pressure and stress, the Newton (N) per square metre (m<sup>2</sup>) and the siemens (S) as a special name for the unit of electrical conductance. In 1975 the CGPM adopted the becquerel (Bq) as the unit of the activity of radionuclides and the gray (Gy) as the unit for absorbed dose.

### **2. International Bureau of Weights and Measures**

2.1 The Bureau International des Poids et Mesures (BIPM) was set up by the Metre Convention signed in Paris on 20 May 1875 by 17 States during final session of the Diplomatic Conference of the Metre. This Convention was amended in 1921. BIPM has its headquarters near Paris and its upkeep is financed by the Member States of the Metre Convention. The task of BIPM is to ensure world-wide unification of physical measurements; it is responsible for:

- establishing the fundamental standards and scales for measurement of the principal physical quantities and maintaining the international prototypes;
- carrying out comparisons of national and international standards;
- ensuring the co-ordination of corresponding measuring techniques;
- carrying out and co-coordinating the determinations relating to the fundamental physical constants.

2.2 BIPM operates under the exclusive supervision of the International Committee of Weights and Measures (CIPM) which itself comes under the authority of the General Conference of Weights and Measures (CGPM). The International Committee consists of 18 members each belonging to a different State; it meets at least once every two years. The officers of this Committee issue an Annual Report on the administrative and financial position of BIPM to the Governments of the Member States of the Metre Convention.

2.3 The activities of BIPM, which in the beginning were limited to the measurements of length and mass and to metrological studies in a relation to these quantities, have been extended to standards of measurement for electricity (1927), photometry (1937) and ionizing radiations (1960). To this end the

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

original laboratories, built in 1876-78, were enlarged in 1929 and two new buildings were constructed in 1963-64 for the ionizing radiation laboratories. Some 30 physicists or technicians work in the laboratories of BIPM. They do metrological research, and also undertake measurement and certification of material standards of the above-mentioned quantities.

2.4 In view of the extension of the work entrusted to BIPM, CIPM has set up since 1927, under the name of Consultative Committees, bodies designed to provide it with information on matters which it refers to them for study and advice. These Consultative Committees, which may form temporary or permanent working groups to study special subjects, are responsible for coordinating the international work carried out in their respective fields and proposing recommendations concerning the amendment to be made to the definitions and values of units. In order to ensure world-wide uniformity in units of measurement, the International Committee accordingly acts directly or submits proposals for sanction by the General Conference.

2.5 The Consultative Committees have common regulations (Proces-Verbaux CIPM, 1963, 31,97). Each Consultative Committees, the chairman of which is normally a member of CIPM, is composed of the delegate from each of the large metrology laboratories and specialized institutes, a list of which is drawn up by CIPM, as well as individual members also appointed by CIPM and one representative of BIPM. These Committees hold their meetings at irregular intervals; at present there are seven of them in existence as follows:

1. The Consultative Committee for Photometry and Radiometry (CCPR), which is the new name given in 1971 to the Consultative Committee for Photometry, set up in 1933 (between 1930 and 1933 the preceding committee (CCE) dealt with matters concerning photometry).
2. The Consultative Committee for Thermometry (CCT) set up in 1937.

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

3. The Consultative Committee for the Definition of the Metre (CCDS), set up in 1952.
4. The Consultative Committee for the Definition of the Second (CCDS), set up in 1956.
5. The Consultative Committee for the Standards of Measurement of Ionizing Radiation (CCEMRI), set up in 1958. Since 1969 this Consultative Committee has consisted of four sections: Section I (measurement of X and  $\gamma$ -rays); Section II (measurement of radio-nuclides); Section III (neutron measurements); Section IV (a-energy standards).
6. The Consultative Committee for Units (CCU) set up in 1964.

The proceedings of the General Conference, the International Committee, the Consultative Committee and the International Bureau are published under the auspices of the latter in the following series:

- Comptes rendus des séances de la Conference Generale des Poids et Mesures;
  - Proces-Verbaux des séances du Comite International des Poids et Mesures;
  - Sessions des comites Consultatifs;
  - Recueil de Travaux du Bureau International des Poids et Mesures (this compilation bring together articles published in scientific and technical journals and books, as well as certain work published in the form of duplicated reports).
- 2.6 From time to time BIPM publishes a report on the development of the metric system throughout the world, entitled *Les recents progress du System Metrique. The collection of the Travaux et Memoires du Bureau International des Poids et Mesures* (22 volumes published between 1881 and 1966) ceased in 1966 by a decision of the CIPM. Since 1965 the international journal *Metrologia*, edited under the auspices of CIPM, has published articles on the more important work on scientific metrology

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

carried out throughout the world, on the improvement in measuring methods and standards, of units, etc, as well as reports concerning the activities, decisions and recommendations of the various bodies created under the Metre Convention.

3. International Organization for Standardization The International Organization for Standardization (ISO) is world-wide federation of national standards institutes which, although not a part of the BIPM, provides recommendations for the use of SI and certain other units. ISO Document 1000 and the ISO Recommendation R31 series of documents provides extensive detail on the application of the SI units. ICAO maintains liaison with ISO regarding the standardized application of SI units in aviation.

**INTENTIONALLY LEFT BLANK**

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

---

### ATTACHMENT 20 B

#### GUIDANCE ON THE APPLICATION OF THE SI

##### 1. Introduction

1.1 The International System of Units is a complete, coherent system which includes three classes of units:

- a.) base units;
- b.) supplementary units; and
- c.) derived units.

1.2 The SI is based on seven units which are dimensionally independent and are listed in Table B-1.

*Table B-1. SI base units*

<i>Quantity</i>	<i>Unit</i>	<i>Symbol</i>
<i>Amount of a substances</i>	<i>mole</i>	<i>mol</i>
<i>Electric current</i>	<i>ampere</i>	<i>A</i>
<i>Length</i>	<i>metre</i>	<i>m</i>
<i>Luminous intensity</i>	<i>candela</i>	<i>cd</i>
<i>Mass</i>	<i>kilogram</i>	<i>kg</i>
<i>Thermodynamic temperature</i>	<i>Kevin</i>	<i>K</i>
<i>Time</i>	<i>second</i>	<i>s</i>

1.3. *The supplementary units of the SI are listed in Table B-2 and may be regarded either as base units or as derived units.*

<i>Quantity</i>	<i>Unit</i>	<i>Symbol</i>
<i>Plane angle</i>	<i>radian</i>	<i>rad</i>
<i>Solid angle</i>	<i>steradian</i>	<i>sr</i>

1.4 *Derived units of the SI are formed by combining base units, supplementary units and other derived units according to the algebraic relations linking the*

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

---

corresponding quantities. The symbols for derived units are obtained by means of the mathematical signs for multiplication, division and the use of exponents. Those derived SI units which have special names and symbols are listed in Table B-3. Note. – The specific application of the derived units listed in Table B-3 and other units common to international civil aviation operation is given in Table 3- 4.

Table B-3 SI derived units with special names

Quantity	Unit	Symbol	derivation
Absorbed dose (radiation)	gray	Gy	J/kg
activity of radionuclides	Becquerel	Bq	1/s
capacitance	farad	F	C/ V
conductance	siemens	S	A/ V
dose equivalent (radiation)	sievert	Sv	J/kg
electric potential, Potential difference, electromotive force	volt	V	W/A
electric resistance	ohm	Ω	V/A
energy, work, quantity of heat	joule	J	N.m
force	newton	N	kg. m/s <sup>2</sup>
frequency (of a periodic phenomenon)	hertz	Hz	1/s
illuminance	lux	lx	lm/m <sup>2</sup>
inductance	henry	H	Wb/A
luminous flux	lumen	lm	cd.sr
magnetic flux	weber	Wb	V.s
magnetic flux density	tesla	T	Wb.m <sup>2</sup>
power, radiant flux	watt	W	J/s
pressure, stress	pascal	Pa	N/m <sup>2</sup>
quantity of electricity, electric charge	coulomb	C	A.s

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

- 1.5 The SI is a rationalized selection of units from the metric system which individually are not new. The great advantage of SI is that there is only one unit for each physical unit quantity- the metre for length, kilogram (instead of gram) for mass, second for time, etc. From these elemental or base units, units for all other mechanical quantities are derived. These derived units are defined by simple relationship such as velocity equals rate of change of distance, acceleration equals rate of change of velocity, force is the product of mass and acceleration, work and energy is the product of force and distance, power is work done per unit time, etc. Some of these units have only generic names such as metre per second for velocity; others have special names such as Newton (N) for force, joule (J) for work or energy, watt (W) for power. The SI units for force, energy and power are the same regardless of whether the process is mechanical, electrical, chemical or nuclear. A force of 1 Newton applied for a distance of 1 metre can produce 1 joule of heat, which is identical with what 1 watt of electric power can produce in 1 second.
- 1.6 Corresponding to the advantages of SI, which result from the use of a unique unit of each physical quantity, are the advantages which result from the use of a unique and well-defined set of symbols and abbreviations. Such symbols and abbreviations eliminate the confusion that can arise from current practices in different disciplines such as the use of “b” for both the bar (a unit of pressure) and barn (a unit of area).
- 1.7 Another advantage of SI is its retention of the decimal relation between multiplies and sub-multiplies of the base units for each physical quantity. Prefixes are established for designating multiple and sub-multiple units from (“exa”) ( $10^{18}$ ) down to (“atto”) ( $10^{-18}$ ) for convenience in writing and speaking.
- 1.8 Another major advantage of SI is its coherence. Units might be chosen arbitrarily, but making an independent choice of a unit for each category of mutually comparable quantities would lead in general to the appearance of several additional numerical factors in the equations between the numeric

values. It is possible, however, and in practice more convenient, to choose a system of units in such a way that the equation between numerical values, including the numerical factors, have exactly the same form as the corresponding equations between the quantities. A unit system defined in this way is called coherent with respect to the system of quantities and equations in question. Equations between units of a coherent unit system contain as numerical factors only the number 1. In a coherent system a product or quotient of any two unit quantities is the unit of the resulting quantity. For example, in any coherent system, unit area results when unit length is multiplied by unit length, unit velocity when unit length is divided by unit time and unit force when unit mass is multiplied by unit acceleration.

Note. - Figure B-1 illustrates the relationships of the units of the SI.

### **2. Mass, force and weight**

2.1 The principal departure of SI from the gravimetric system of metric engineering units is the use of explicitly distinct units from mass and force. In SI the name kilogram is restricted to the unit of mass, and the kilogram-force (from dropped) is not to be used. In its place the SI unit of force, the Newton is used. Likewise, the Newton rather than the kilogram-force is used to form derived units which include force, for example, pressure or stress ( $\text{N}/\text{m}^2 = \text{Pa}$ ), energy ( $\text{N} \cdot \text{m} = \text{J}$ ), and power ( $\text{N} \cdot \text{m}/\text{s} = \text{W}$ ).

2.2 Considerable confusion exists in the use the term weight as a quantity to mean either force or mass. In common use, the term weight nearly always means mass; thus when one speaks of a person's weight, the quantity referred is mass. In science and technology, the term weight of a body has usually meant the force that, if applied to the body, would give it an acceleration equal to the local acceleration of free fall. The adjective "local" in phrase "local acceleration of free fall" has usually meant a location on the surface of the earth; in this context the "local acceleration of free fall" has the symbol  $g$  (sometimes referred to as "acceleration of gravity") with observed values of  $g$  differing by

over 0.5 percent at various points on the earth's surface and decreasing as distance from the earth is increased. Thus, because weight is a force = mass x acceleration due to gravity, a person's weight is conditional on his location, but mass is not. A person with a mass of 70 kg might experience a force (weight) on earth of 686 newtons (=155 lbf) and a force weight of only 113 newtons (=22 lbf) on the moon. Because of the dual use of the term weight as a quantity, the term weight should be avoided in technical practice except under circumstances in which its meaning is completely clear. When the term is used, it is important to know whether mass or force is intended and to use SI units properly by using kilograms for mass or newtons for force.

- 2.3 *Gravity* is involved in determining mass with a balance or scale. When a standard mass is used to balance the measured mass, the direct effect of gravity on the two masses is cancelled, but the indirect effect through the buoyancy of air or other fluid is generally not cancelled. In using a spring scale, mass is measured indirectly, since the instrument responds to the force of gravity. Such scales may be calibrated in mass units if the variation in acceleration of gravity and buoyancy corrections are not significant in their use.

### **3. Energy and torque**

- 3.1 The vector product of force and moment arm is widely designated by the unit Newton metre. This unit for bending moment or torque results in confusion with the unit for energy, which is also Newton metre. If torque is expressed as newton metre per radian, the relationship to energy is clarified, since the product of torque and angular rotation is energy:

$$\mathbf{(N \cdot m / rad) \cdot rad = N \cdot m}$$

- 3.2 If vectors were shown, the distinction between energy and torque would be obvious, since the orientation of force and length is different in the two cases.

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

It is important to recognize this difference in using torque and energy, and the joule should never be used for torque.

### **4. SI prefixes**

#### 4.1 Selection of prefixes

4.1.1 In general the SI prefixes should be used to indicate orders of magnitude, thus eliminating non-significant digit and leading zeros in decimal fractions, and providing a convenient alternative to the powers-of-ten notation preferred in computation. For examples:

**12 300 mm becomes 12.3 m**

**12.3 x 10<sup>3</sup> m becomes 12.3 km**

**0.00123 μ A becomes 1.23 nA**

4.1.2 When expressing a quantity by a numerical value and a unit, prefixes should preferably be chosen so that the numerical value lies between 0.1 and 1000. To minimize variety, it is recommended that prefixes representing powers of 1 000 be used. However, in the following cases, deviation from the above may be indicated:

- a) In expressing area and volume, the prefixes hector, deca, deci and centi may be required: for example, square hectometer, cubic centimeter;
- b) In tables of values of the name quantity, or in a discussion of such values within a given context, it is generally preferable to use the same unit multiple throughout; and
- c) For certain quantities in particular applications, one particular multiple are customarily used. For example, the hectopascal is used for altimeter setting and the millimetre is used for linear dimensions in mechanical engineering drawings even when the values lie outside the range 0.1 to 1000.

4.2 Prefixes in compound units It is recommended that only one prefix be used in forming a multiple of a compound unit. Normally the prefix should be

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

attached to a unit in the numerator. One exception to this occurs when the kilogram is one of the units. For example: V/m, mV/mm; MJ/kg, not kJ/g

### 4.3 Compound prefixes

Compound prefixes, formed by the juxtaposition of two or more SI prefixes, are not to be used. For example:

1nm not 1m $\mu$ m; 1 pF not 1 $\mu$  $\mu$ F

If values are required outside the range covered by the prefixes, they should be expressed using powers of ten applied to the base unit.

### 4.4 Powers of units

An exponent attached to a symbol containing a prefix indicates that the multiple or sub-multiple of the unit (the unit with its prefix) is raised to the power expressed by the exponent. For Example:

$$1 \text{ cm}^3 = (10^{-2}\text{m})^3 = 10^{-6} \text{ m}^3$$

$$1 \text{ ns}^{-1} = (10^{-9}\text{s})^{-1} = 10^9 \text{ s}^{-1}$$

$$1\text{mm}^2/\text{s} = (10^{-3}\text{m})^2/\text{s} = 10^{-6} \text{ m}^2/\text{s}$$

## **5. Style and usage**

### 5.1 Rules for writing unit symbols

5.1.1 Units symbols should be printed in roman (upright) type regardless of the type style used in the surrounding text.

5.1.2 Unit symbols are unaltered in the plural.

5.1.3 Unit symbols are not followed by a period except when used at the end of a sentence.

5.1.4 Letter unit symbols are written in lower case (cd) unless the unit name has been derived from a proper name, in which case the first letter of the symbol is capitalized (W, Pa). Prefix and unity symbols retain their prescribed form regardless of the surrounding typography.

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

5.1.5 In the complete expression for a quantity, a space should be left between the numerical value and the unit symbol. For example, write 35 mm not 35mm, and 2.37 1m, not 2.371m. When the quantity is used in an adjectival sense, a hyphen is often used, for example, 35-mm film.

*Exception:* No space is left between the numerical value and the symbol for degree, minute and second of plane angle, and degree Celsius.

5.1.6 No space is used between the prefix and unit symbols.

5.1.7 Symbols, not abbreviations, should be used for units. For examples, use “A”, not “amp”, for ampere.

5.2 Rules for writing unit names

5.2.1 Spelled-out unit names are treated as common nouns in English. Thus, the first letter of a unit name is not capitalized except at the beginning of a sentence or in capitalized material such as a title, even though the unit name may be derived from a proper name and therefore be represented as a symbol by a capital letter (see 5.1.4). For example, normally write “newton” even though the symbol is N.

5.2.2 Plurals are used when required by the rules of grammar and are normally formed regularly, for example, henries for the plural of henry. The following irregular plurals are recommended:

<i>Singular</i>	<i>plural</i>
lux	lux
hertz	hertz
siemens	siemens

5.2.3 No space or hyphen is used between the prefix and the unit name.

5.3 Units formed by multiplication and division

5.3.1 with unit names:

Product, use a space (preferred) or hyphen:  
Newton metre or newton metre

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

---

in the case of the watt hour the space may be omitted, thus:  
Watthour

Quotient, use the word per and not a solidus:  
Metre per second not metre/second

Powers, use the modifier squared or cubed placed after the unit name:  
metre per second squared

In the case of area or volume, a modifier may be placed before the unit name:  
square millimeter, cubic metre.

This exception also applies to derived unit using area or volume:  
watt per square metre.

*Note.* - To avoid ambiguity in complicated expressions, symbols are preferred to words.

### 5.3.2 with unit symbols:

Product may be indicated in either of the following ways:

Nm or N . m for newton metre

*Note.* – When using for a prefix a symbol which coincides with the symbol for the unit, special care should be taken to avoid confusion. The unit newton metre for torque should be written, for example, Nm or N . m to avoid confusion with mN, the millinewton.

An exception to this practice is made for computer printouts, automatic typewriter work, etc., where the dot half high is not possible, and a dot on the line may be used.

Quotient, use one of the following forms:  
m/s or m . s<sup>-1</sup> or  $\frac{m}{s}$

In no case should more than one solidus be used in the same expression unless parentheses are inserted to avoid ambiguity. For example, write:

J/ (mol . k) or J . mol<sup>-1</sup> . k<sup>-1</sup> or (J/mol)/k but not J/mol/k.

### 5.3.3 Symbols and unit names should not be mixed in the same expression.

Write:

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

Joules per kilogram or J/kg or  $J \cdot kg^{-1}$  but not joules/kilogram or joules  $\cdot kg^{-1}$ .

### 5.4 Numbers

5.4.1 The preferred decimal marker is a point on the line (period); however, the comma is also acceptable. When writing numbers less than one, a zero should be written before the decimal marker.

5.4.2 The comma is not to be used to separate digits. Instead, digits should be separated into groups of three, counting from the decimal point towards the left and the right, and using a small space to separate the groups. For example:

73 655                      7 281                      2.567 321                      0. 133 47

The space between groups should be approximately the width of the letter “i” and the width of the space should be constant even if, as is often the case in printing, variable-width spacing is used between the words.

5.4.3 The sign for multiplication of number is a cross (x) Or a dot half high. However, if the dot half high is used as the multiplication sign, a point on the line must not be used as a decimal marker in the same expression.

5.4.4 Attachment of letters to a unit symbol as a means of giving information about the nature of the quantity under consideration is incorrect. Thus MWe for “megawatts electrical (power)”, Vac for “volts ac” and kJt for “kilojoules thermal (energy)” are not acceptable. For this reason, no attempt should be made to construct SI equivalents of the abbreviations “psia” and “psig”, so often used to distinguish between absolute and gauge pressure. If the context leaves any doubt as to which is meant, the word pressure must be qualified appropriately. For example:

“ . . . at a gauge pressure of 13 kpa”.  
or“ . . . at an absolute pressure of 13 kpa”.

**ATTACHMENT 20C.**

**CONVERSION FACTORS**

**1. General**

1.1 The list of conversion factors which is contained in this attachment is provided to express the definitions of miscellaneous units of measure as numerical multiples of SI units.

1.2 The conversion factors are presented for ready adaptation to computer read-out and electronic data transmission. The factors are written as a number greater than 1 and less than 10 with six or less decimal places. This number is followed by the letter E (for exponent), a plus or minus symbol, and two digits which indicate the power of 10 by which the number must be multiplied to obtain the correct value.

For example:

3.523 907 E - 02 is  $3.523\ 907 \times 10^{-2}$  or 0.035 239 07

Similarly,

3.386 389 E + 03 is  $3.386\ 389 \times 10^3$  or 3 386.389

1.3 An asterisk (\*) after the sixth decimal place indicates that the conversion factor is exact and that all subsequent digits are zero. Where less than six decimal places are shown, more precision is not warranted.

1.4 Further examples of use of the tables:

To convert from	to multiply by
Pound-force per square foot	Pa 4.788 026 E+01
Inch	m 2.540 000*E - 02

thus:

$$1 \text{ lbf/ft}^2 = 47.880\ 26 \text{ Pa}$$

## **PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS**

---

1 inch = 0.025 4 m (exactly)

### **2. Factors not listed**

2.1 Conversion factors for compound unit which are not listed herein can easily be developed from numbers given in the list by the substitution of converted units, as follows.

*Example: To find conversion factor of lb. ft/s to kg. m/s:*

*First convert*

1 lb to 0.453 592 4 kg

1 ft to 0.304 8 m

*Then substitute:*

$(0.453\ 592\ 4\ \text{kg}) \times (0.304\ 8\ \text{m})/\text{s} = 0.138\ 255\ \text{kg} \cdot \text{m}/\text{s}$

Thus the factor is 1.382 55 E – 01.]

Table C – 1. Conversion factors to SI units  
(*Symbols of SI units given in parentheses*)

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

---

To convert from	to	Multiply by
abampere	ampere (A)	1.000 000*E + 01
abcoulomb	coulomb (C)	1.000 000*E + 01
abfarad	farad (F)	1.000 000*E + 09
abhenry	henry (H)	1.000 000*E - 09
abmho	siemens (S)	1.000 000*E + 09
abohm	ohm ( $\Omega$ )	1.000 000*E - 09
abvolt	volt (V)	1.000 000*E - 08
acre (U.S survey)	square metre (m <sup>2</sup> )	4.046 873*E + 03
ampere hour	coulomb (C)	3.600 000*E + 03
are	square metre (m <sup>2</sup> )	1.000 000*E + 02
atmosphere (standard)	pascal (Pa)	1.013 250*E +05
atmosphere (technical = 1 kgf/cm <sup>2</sup> )	pascal (Pa)	9.806 650*E + 04
Bar	pascal (Pa)	1.000 000*E + 05
barrel (for petroleum, 42 U.S liquid gal)	cubic metre (m <sup>3</sup> )	1.589 873*E -01

---

\* An asterisk (\*) after sixth decimal place indicates that the conversion factor is exact and that all subsequent digits are zero. Where less than six decimal places are shown, more precision is not warranted.

Table C-1 (cont.)

Table C-1 (cont.)

---

_To convert from	to	multiply by
------------------	----	-------------

---

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

---

British thermal unit (International Table)	joule (J)	1.055 056 E + 03
British thermal unit (mean)	joule (J)	1.055 87 E + 03
British thermal unit (thermochemical)	joule (J)	1.054 350 E + 03
British thermal unit (39°F)	joule (J)	1.059 67 E + 03
British thermal unit (59°F)	joule (J)	1.054 80 E + 03
British thermal unit (60°F)	joule (J)	1.054 68 E + 03
Btu (International Table) . ft/h . ft <sup>2</sup> . °F (k, thermal conductivity)	watt per metre Kelvin (W/m . k)	1.730 735E + 00
Btu (thermochemical) . ft/h . ft <sup>2</sup> . °F (k, thermal conductivity)	watt per metre Kelvin (W/m . k)	1.729 577 E + 00
Btu (International Table) . in/h . ft <sup>2</sup> . °F (k, thermal conductivity)	watt per metre Kelvin (W/m . k)	1.442 279 E – 01
Btu (thermochemical) . in/h . ft <sup>2</sup> . °F (k, thermal conductivity)	watt per metre Kelvin (W/m . k)	1.441 314 E – 01
Btu (International Table) . in/s . ft <sup>2</sup> . °F (k, thermal conductivity)	watt per metre Kelvin (W/m . k)	5.192 204 E + 02
Btu (thermochemical) . in/s . ft <sup>2</sup> . °F (k, thermal conductivity)	watt per metre Kelvin (W/m . k)	5.188 732 E + 02
Btu (International Table)/h	watt (w)	2.930 711 E – 01
Btu (thermochemical)/h	watt (w)	2.928 751 E – 01
Btu (thermochemical)/min	watt (w)	1.757 250 E + 01
Btu (thermochemical)/s	watt (w)	1.054 350 E + 03
Btu (International Table)/ft <sup>2</sup>	joule per square metre (J/m <sup>2</sup> )	1.135 653 E +04
Btu (thermochemical)/ft <sup>2</sup>	joule per square metre (J/m <sup>2</sup> )	1.134 893 E + 04
Btu (thermochemical)/ft <sup>2</sup> . h	watt per square metre (w/m <sup>2</sup> )	3.152 481 E + 00
Btu (thermochemical)/ft <sup>2</sup> . min	watt per square metre (w/m <sup>2</sup> )	1.891 489 E +02
Btu (thermochemical)/ft <sup>2</sup> . s	watt per square metre (w/m <sup>2</sup> )	1.134 893 E + 04
Btu (thermochemical)/in <sup>2</sup> . s	watt per square metre (w/m <sup>2</sup> )	1.634 246 E + 06
Btu (International Table)/h . ft <sup>2</sup> . °F (C, thermal conductance)	watt per square metre kelvin (W/m <sup>2</sup> . k)	5.678 263 E + 00
Btu (thermochemical)/h . ft <sup>2</sup> . °F (C, thermal conductance)	watt per square metre kelvin (W/m <sup>2</sup> . k)	5.674 466 E + 00
Btu (International Table)/s . ft <sup>2</sup> . °F	watt per square metre Kelvin (W/m <sup>2</sup> . k)	2.044 175 E + 04
Btu (thermochemical)/s . ft <sup>2</sup> . °F	watt per square metre kelvin(W/m <sup>2</sup> . k)	2.042 808 E + 04
Btu (International Table)/lb	joule per kilogram (J/kg)	2.326 000*E + 03
Btu (thermochemical)/lb	joule per kilogram (J/kg)	2.324 444 E +03

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

Table C-1 (cont.)

To convert from	to	multiply by
Btu (International Table)/lb . of (c, heat capacity)	joule per kilogram (J/kg)	4.186 800*E + 03
Btu (thermochemical)/lb . oF (c, heat capacity)	joule per kilogram (J/kg)	4.184 000 E + 03
calibre (inch)	metre (m)	2.540 000*E – 02
calorie (International Table)	joule (J)	4.186 800*E + 00
calorie (mean)	joule (J)	4.190 02 E + 00
calorie (thermochemical)	joule (J)	4.184 000*E + 00
calorie (15°C)	joule (J)	4.185 80 E + 00
calorie (20°C)	joule (J)	4.181 90 E + 00
calorie (kilogram, InternationalTable)	joule (J)	4.186 800*E + 03
calorie (kilogram, mean)	joule (J)	4.190 02 E + 03
calorie (kilogram, thermochemical)	joule (J)	4.184 000*E + 03
cal (thermochemical)/cm <sup>2</sup>	joule (J)	4.184 000*E + 04
cal (International Table)/g	joule per kilogram (J/kg)	4.186 800*E +03
cal (thermochemical)/g	joule per kilogram (J/kg)	4.184 000*E +03
cal (International Table)/g . °c	joule per kilogram kelvin (J/kg . k)	4.186 800*E + 03
cal (thermochemical)/g . °C	joule per kilogram kelvin (J/kg . k)	4.181 000*E + 03
cal (thermochemical)/min	watt (W)	6.973 333*E + 02
cal (thermochemical)/s	watt (W) 4.184 000*E + 00	
cal (thermochemical)/cm <sup>2</sup> . min	watt per square metre(W/m <sup>2</sup> )	6.973 333 E +02
cal (thermochemical)/cm <sup>2</sup> . s	watt per square metre (W/m <sup>2</sup> )	4.184 000*E +04
cal (thermochemical)/cm <sup>2</sup> . s . °C	watt per metre kelvin (W/m. k)	4.184 000*E +02
centimeter of mercury (0°C)	pascal (Pa)	1.333 22 E +03
centimeter of water (4°C)	pascal (Pa)	9.806 38 E +01
centipoises	pascal second (Pa . s)	1.000 000*E - 03
centistokes	metre squared per second (m <sup>2</sup> /s)	1.000 000*E - 06
circular mil	square metre (m <sup>2</sup> )	5.067 075 E - 10
clo	kelvin metre squared per watt (K . m <sup>2</sup> /W)	2.003 712 E - 01
cup	cubic metre (m <sup>3</sup> )	2.365 882 E - 04
curie	becquerel (Bq)	3.700 000*E +01
day (mean solar)	second (s)	8.640 000 E +04
day (sidereal)	second (s)	8.616 409 E +04
degree (angle)	radian (rad)	1.745 329 E - 02

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

oF . h . ft <sup>2</sup> /Btu (International Table)	kelvin metre squared per watt	1.761 102 E - 01
(R, thermal resistance)	(K . m <sup>2</sup> /W )	
oF . h . ft <sup>2</sup> /Btu (International Table)	kelvin metre squared per watt	1.762 280 E - 01
(R, thermal resistance)	(K . m <sup>2</sup> /W )	
dyne	newton (N)	1.000 000*E -05
dyne . cm	Newton metre (N . m)	1.000 000*E -07
dyne/cm <sup>2</sup>	pascal (Pa)	1.000 000*E -01

Table C-1 (cont.)

To convert from	to	multiply by
electron volt	joule (J)	1.602 19 E - 19
EMU of capacitance	farad (F)	1.000 000*E + 09
EMU of current	ampere (A)	1.000 000*E +01
EMU of electric potential	Volt (V)	1.000 000*E -08
EMU of inductance	henry (H)	1.000 000*E - 09
EMU of reresistance	ohm (Ω)	1.000 000*E - 09
Erg	joule (J)	1.000 000*E - 07
Erg/cm <sup>2</sup> . s	watt per square metre (W/m <sup>2</sup> )	1.000 000*E - 03
Erg/s	watt (W)	1.000 000*E - 07
ESU of capacitance	farad (F)	1.112 650*E - 12
ESU of current	ampere (A)	3.335 6 E - 10
ESU of electric potential	volt (V)	2.997 9 E + 02
ESU of inductance	henry (H)	8.987 554 E + 11
ESU of resistance	ohm(Ω)	8.987 554 E + 11
faraday (based on carbon-12)	coulomb (C)	9.648 70 E + 04
faraday (chemical)	coulomb (C)	9.649 57 E + 04
faraday (physical)	coulomb (C)	9.652 19 E + 04
fathom	metre (m)	1.828 8 E + 00
fermi (femtometre)	metre (C)	1.000 000*E - 15
fluid ounce (U.S)	cubic metre (m <sup>3</sup> )	2.957 353 E - 05
foot	metre (m)	3.048 000 E - 01
foot (U.S survey)	metre (m)	3.048 006 E - 01
foot of water (39.2°F)	pascal (Pa)	2.988 98 E + 03
ft <sup>2</sup>	square metre (m <sup>2</sup> )	9.290 304*E - 02
ft <sup>2</sup> /h (thermal diffusivity)	metre squared per second (m <sup>2</sup> /s)	2.580 640*E - 05
ft <sup>2</sup> /s	metre squared per second (m <sup>2</sup> /s)	9.290 304*E - 02
ft <sup>3</sup> (volume; section modulus)	cubic metre (m <sup>3</sup> )	2.831 685 E - 02
ft <sup>3</sup> /min	cubic metre per second (m <sup>3</sup> /s)	4.719 474 E - 04
ft <sup>3</sup> /s	cubic metre per second (m <sup>3</sup> /s)	2.831 685 E - 02
ft <sup>4</sup> (moment of section)	metre to fourth power (m <sup>3</sup> )	8.630 975 E - 03
ft . lbf/	joule (J)	1.355 818 E + 00

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

ft . lbf/h	watt (W)	3.766 161 E - 04
ft . lbf/min	watt (W)	2.259 697 E - 02
ft . lbf/s	watt (W)	1.355 818 E + 00
ft . poundal	joule (J)	4.214 011 E - 02
free fall, standard (g)	metre per second squared (m/s <sup>2</sup> )	9.806 650*E +00
ft/h	metre per second (m/s)	8.466 667 E - 05
ft/min	metre per second (m/s)	5.080 000*E - 03
ft/s	metre per second (m/s)	3.048 000*E - 01
ft/s <sup>2</sup>	metre per second squared (m/s <sup>2</sup> )	3.048 000*E - 01
footcandle	lux (lx)	1.076 391 E +01
footlambert	candela per square metered (cd/m <sup>2</sup> )	3.426 295 E + 00
gal	metre per second squared (m/s <sup>2</sup> )	1.000 000*E - 02
gallon (Canadian liquid)	cubic metre (m <sup>3</sup> )	4.546 090 E - 03
gallon (U.K. liquid)	cubic metre (m <sup>3</sup> )	4.546 092 E - 03
gallon (U.S. dry)	cubic metre (m <sup>3</sup> )	4.404 884 E - 03
gallon (U./S. liquid)	cubic metre (m <sup>3</sup> )	3.785 412 E - 03

Table C-1 (cont.)

_To convert from	to	multiply by
—		
gal (U.S. liquid)/day	cubic metre per second (m <sup>3</sup> /s )	4.381 264 E - 08
gal (U.S. liquid)/min	cubic metre per second (m <sup>3</sup> /s)	6.309 020 E - 05
gal (U.S. liquid)/hp. H (SFC, specific fuel consumption)	cubic metre per joule (m <sup>3</sup> /J)	1.410 089 E-09
gamma	tesla (T)	1.000 000*E - 09
gauss	tesla (T)	1.000 000*E -04
gilbert	ampere (A)	7.957 745 E-01
grad	degree (angular)	9.000 000*E-01
grad	radian (rad)	1.570 796 E-02
gram	kilogram (kg)	1.000 000*E-03
g/cm <sup>3</sup>	kilogram per cubic metre (kg/m <sup>3</sup> )	1.000 000*E+03
gram-force/cm <sup>2</sup>	pascal (Pa)	9.806 650*E+01
hectare	square metre (m <sup>2</sup> )	1.000 000*E+04
horsepower (550 ft . lbf/s)	watt (W)	7.456 999 E+02
horsepower (electric)	watt (W)	7.460 000*E+02
horsepower (metric)	watt (W)	7.354 99 E+02
horsepower (water)	watt (W)	7.460 43 E +02
horsepower (U.K.)	watt (W)	7.457 0 E+02
hour (mean solar)	second(s)	3.600 000 E+03
hour (sidereal)	second (s)	3.590 170 E+03
hundredweight (long)	kilogram (kg)	5.080 235 E+01

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

---

hundredweight (short)	kilogram (kg)	4.535 925 E+01
inch	metre (m)	2.540 000*E-02
inch of mercury (32°F)	pascal (Pa)	3.386 38 E+03
inch of mercury (60°F)	pascal (Pa)	3.376 85 E+03
inch of water (39.2°F)	pascal (Pa)	2.490 82 E+02
inch of water (60°F)	pascal (Pa)	2.488 4 E +02
in <sup>2</sup>	square metre (m <sup>2</sup> )	6.451 600*E+04
in <sup>3</sup> (volume; section modulus)	cubic metre (m <sup>3</sup> )	1.638 706 E-05
in <sup>3</sup> /min	cubic metre per second (m <sup>3</sup> /s)	2.731 177 E-07
in <sup>4</sup> (moment of section)	metre to the fourth power (m <sup>4</sup> )	4.162 314 E-07
in/s	metre per second (m/s)	2.540 000*E-02
in/s <sup>2</sup>	metre per second squared (m/s <sup>2</sup> )	2.540 000*E-02
kilocalorie (International Table)	joule (J)	4.186 800*E+03
kilocalorie (mean)	joule (J)	4.190 02 E+03
kilocalorie (thermochemical)	joule (J)	4.184 000*E+03
kilocalorie (thermochemical)/min	watt (W)	6.973 333 E+01
kilocalorie (thermochemical)/s	watt (W)	4.184 000*E+03
kilogram-force (kgf)	newton (N)	9.806 650*E+00
kgf . m	newton metre (N . m)	9.806 650*E+00
kgf . s <sup>2</sup> /m (mass)	kilogram (kg)	9.806 650*E+00
kgf/cm <sup>2</sup>	pascal (Pa)	9.806 650*E+04

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

Table C-1 (cont.)

_To convert from	to	multiply by
—		
kgf/m <sup>2</sup>	pascal (Pa)	9.806 650*E+00
kgf/mm <sup>2</sup>	pascal (Pa)	9.806 650*E+06
km/h	metre per second (m/s)	2.777 778 E-01
kilopond	newton (N)	9.806 650*E+00
kW . h	joule (J)	3.600 000*E+06
kip (1 000 lbf)	newton (N)	4.448 222 E+03
kip/in <sup>2</sup> (ksi)	pascal (Pa)	6.894 757 E+06
knot (international)	meter per second (m/s)	5.144 444 E-01
lambert	candela per square metre (cd/m <sup>2</sup> )	1/ π *E+04
lambert	candela per square metre (cd/m <sup>2</sup> )	3.183 099 E+03
langery	joule per square metre (J/m <sup>2</sup> )	4.184 000*E-02
lb . ft <sup>2</sup> (moment of inertia)	kilogram metre squared (kg . m <sup>2</sup> )	4.214 011 E-02
lb . in <sup>2</sup> (moment of inertia)	kilogram metre squared (kg . m <sup>2</sup> )	2.926 397 E-04
lb/ft . h	pascal (Pa . s)	4.133 789 E-04
lb/ft . s	pascal (Pa . s)	1.488 164 E+00
lb/ft <sup>2</sup>	kilogram per square metre (kg/m <sup>2</sup> )	4.882 428 E+00
lb/ft <sup>3</sup>	kilogram per cubic metre (kg/m <sup>3</sup> )	1.601 486 E+01
lb/gal (U.K. liquid)	kilogram per cubic metre (kg/m <sup>3</sup> )	9.977 633 E+01
lb/gal (U.S. liquid)	kilogram per cubic metre (kg/m <sup>3</sup> )	1.198 264 E+02
lb/h	kilogram per second (kg/s)	1.259 979 E-04
lb/hp . h (SFC, specific fuel consumption)	kilogram per joule (kg/J)	1.689 659 E-07
lb/in <sup>3</sup>	kilogram per cubic metre (kg/m <sup>3</sup> )	2.769 990 E+04
lb/min	kilogram per second (kg/s)	7.559 873 E-03
lb/s	kilogram per second (kg/s)	4.535 924 E-01
lb/yd <sup>3</sup>	kilogram per cubic metre (kg/m <sup>3</sup> )	5.932 764 E-01
lbf. Ft	newton metre (N . m)	1.355 818 E+00
lbf . ft/in	newton metre per metre (N . m/m)	5.337 866 E+01
lbf . in	newton metre (N . m)	1.129 848 E-01
lbf . in/in	newton metre per metre (N . m/m)	4.448 222 E+00
lbf . s/ft <sup>2</sup>	pascal second (Pa . s)	4.788 026 E+01
lbf/ft	newton per metre (N/m)	1.459 390 E+01
lbf/ft <sup>2</sup>	pascal (Pa)	4.788 026 E+01
lbf/in	Newton per metre (N/m)	1.751 268 E +02
lbf/in <sup>2</sup> (psi)	pascal (Pa)	6.894 757 E+03
lbf/lb (thrust/weight (mass) ratio)	Newton per kilogram (N/kg)	9.806 650 E+00
light year	metre (m)	9.460 55 E+15
litre	cubic metre (m <sup>3</sup> )	1.000 000*E-03

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

maxwell	weber (wb)	1.000 000*E-08
mho	siemens (S)	1.000 000*E+00
micromicron	metre (m)	2.540 000*E-08
micron	metre (m)	1.000 000*E-06
mil	metre (m)	2.540 000*E-05
mile (international)	metre (m)	1.609 344*E+03
mile (statute)	metre (m)	1.609 3 E+03

Table C-1 (cont.)

To convert from	to	multiply by
___mile (U.S. survey)	metre (m)	1.609 347 E+03
mile (international nautical)	metre (m)	1.852 000*E+03
mile (U.K. nautical)	metre (m)	1.853 184*E+03
mile (U.S. nautical)	metre (m)	1.852 000*E+03
mi <sup>2</sup> (international)	square metre (m <sup>2</sup> )	2.589 988 E+06
mi <sup>2</sup> (U.S. survey)	square metre (m <sup>2</sup> )	2.589 998 E+06
mi/h (international)	metre per second (m/s)	4.470 400*E-01
mi/h (international)	kilometer per hour (km/h)	1.609 344*E+00
mi/min (international)	metre per second (m/s)	2.682 240*E+01
mi/s (international)	metre per second (m/s)	1.609 344*E+03
millibar	pascal (Pa)	1.000 000*E+02
millimeter of mercury (0oC)	pascal (Pa)	1.333 22 E+02
minute (angle)	radian (rad)	2.908 882 E-04
minute (mean solar)	second (s)	6.000 000 E+01
minute (sidereal)	second (s)	5.983 617 E+01
month (mean calendar)	second (s)	2.628 000 E+06
oersted	ampere per metre (A/m)	7.957 747 E+01
ohm centimeter	ohm metre (Ω . m)	1.000 000*E-02
ohm circular-mil per ft	ohm millimetre squared per metre (Ω . mm <sup>2</sup> /m)	1.662 426 E-03
ounce (avoirdupois)	kilogram (kg)	2.834 952 E-02
ounce (troy or apothecary)	kilogram (kg)	3.110 348 E-02
ounce (U.K. fluid)	cubic metre (m <sup>3</sup> )	2.841 307 E-05
ounce (U.K. fluid)	cubic metre (m <sup>3</sup> )	2.957 353 E-05
ounce-force	newton (N)	2.780 139 E-01
ozf . in	newton (N . m)	7.061 552 E-03
oz (avoirdupois)/gal (U.K. liquid)	kilogram per cubic metre (kg/m <sup>3</sup> )	6.236 021 E+00
oz (avoirdupois)/gal (U.S liquid)	kilogram per cubic metre (kg/m <sup>3</sup> )	7.489 152 E+00
oz (avoirdupois)/in <sup>3</sup>	kilogram per cubic metre (kg/m <sup>3</sup> )	1.729 994 E+03

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

oz (avoirdupois)/ft <sup>2</sup>	kilogram per square metre (kg/m <sup>2</sup> )	3.051 517 E-01
oz (avoirdupois)yd <sup>2</sup>	kilogram per square metre (kg/m <sup>2</sup> )	3.390 575 E-02
parsec	metre (m)	3.085 678 E+16
pennyweight	kilogram (kg)	1.555 174 E-03
perm (0°C)	kilogram per pascal second metre squared (kg/Pa . s . m <sup>2</sup> )	5.721 35 E-11
perm . in (23°C)	kilogram per pascal second metre squared (kg/Pa . s . m <sup>2</sup> )	5.745 25 E -11
perm . in (0°C)	kilogram per pascal second metre (kg/Pa . s . m)	1.453 22 E-12

Table C-1 (cont.)

_To convert from	to	multiply by
perm . in (23°C)	kilogram per pascal second metre (kg/Pa . s . m)	1.459 29 E-12
phot	lumen per square metre (lm/m <sup>2</sup> )	1.000 000*E+04
pint (U.S. dry)	cubic metre (m <sup>3</sup> )	5.506 105 E-04
pint (U.S. liquid)	cubic metre (m <sup>3</sup> )	4.731 765 E-04
poise (absolute viscosity)	pascal second (Pa . s)	1.000 000*E-01
pound (lb avoirdupois)	kilogram (kg)	4.535 924 E-01
pound (troy or apothecary)	kilogram (kg)	3.732 417 E-01
poundal	kilogram (kg)	1.382 550 E-01
poundal/ft <sup>2</sup>	newton (N)	1.448 164 E+00
poundal . s/ft <sup>2</sup>	pascal (Pa)	1.448 164 E+00
pound-force (lbf)	newton (N)	4.448 222 E+00
quart (U.S. dry)	cubic (m <sup>3</sup> )	1.101 221 E-03
quart (U.S. liquid)	cubic (m <sup>3</sup> )	9.463 529 E-04
rad (radiation dose absorbed)	gray (Gy)	1.000 000*E-02
rem	sievert (Sv)	1.000 000*E-02
rhe	1 per pascal second (1/Pa . s)	1.000 000*E+01
roentgen	coulomb per kilogram (C/kg)	2.58 E-04
second (angle)	radiant (rad)	4.848 137 E-06
second (sidereal)	second (s)	9.972 696 E-01

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

---

slug	kilogram (kg)	1.459 390 E+01
slug/ft . s	pascal second (Pa . s)	4.788 026 E+01
slug/ft <sup>3</sup>	kilogram per cubic metre (kg/m <sup>3</sup> )	5.153 788 E+02
statampere	ampere (A)	3.335 640 E-10
statcoulomb	coulomb (C)	3.335 640 E-10
statfarad	farad (F)	1.112 650 E-12
stathenry	henry (H)	8.987 554 E+11
statmho	siemens (S)	1.112 650 E-12
statohm	ohm ( $\Omega$ )	8.987 554 E+11
statvolt	volt (V)	2.997 925 E+02
stere	cubic metre (m <sup>3</sup> )	1.000 000*E+00
stilb	candela per square metre (cd/m <sup>2</sup> )	1.000 000*E+04
stokes (kinematic viscosity)	metered squared per second (m <sup>2</sup> /s)	1.000 000*E-04
therm	joule (J)	1.055 056 E+08
ton (assay)	kilogram (kg)	2.916 667 E-02
ton (long, 2 240 lb)	kilogram (kg)	1.016 047 E+03
ton (metric)	kilogram (kg)	1.000 000*E+03
ton (nuclear equivalent of TNT)	joule (J)	4.184 E+09
ton (refrigeration)	watt (W)	3.516 800 E+03
ton (register)	cubic metre (m <sup>3</sup> )	2.831 685 E+00
ton (short, 2 000 lb)	kilogram (kg)	9.071 847 E+02
ton (long)/yd <sup>3</sup>	kilogram per cubic metre (kg/m <sup>3</sup> )	1.328 939 E+03
ton (short)/h	kilogram per cubic second (kg/s)	2.519 958 E-01

Table C-1 (cont.)

_To convert from	to	multiply by
ton-force (2 000 lbf)	newton (N)	8.896 444 E+03
tonne	kilogram (kg)	1.000 000*E+03
torr (mm Hg,0°C)	pascal (Pa)	1.333 22 E+02
unit pole	weber (Wb)	1.256 637 E-07
W . h	joule (J)	3.600 000*E+03
W . s	joule (J)	1.000 000*E+00
W/cm <sup>2</sup>	watt per square metre (W/m <sup>2</sup> )	1.000 000*E+04
W/in <sup>2</sup>	watt per square metre (W/m <sup>2</sup> )	1.550 003 E+03
yard	metre (m)	9.144 000*E-01
yd <sup>2</sup>	square metre (m <sup>2</sup> )	8.361 274 E-01
yd <sup>3</sup>	cubic metre (m <sup>3</sup> )	7.645 549 E-01

## PART 20 - UNITS OF MEASUREMENT TO BE USED IN AIR AND GROUND OPERATIONS

---

yd <sup>3</sup> /min	cubic metre per second (m <sup>3</sup> /s)	1.274 258 E-02
year (calendar)	second (s)	3.153 600 E+07
year (sidereal)	second (s)	3.155 815 E+07
year (tropical)	second (s)	3.155 693 E+07

Table C-2. Temperature conversion formulae

To convert from	to	multiply by
—		
Celsius temperature (t °C)	Kelvin temperature (tk)	$tk = t\text{ }^{\circ}C + 273.15$
Fahrenheit temperature (t °F)	Celsius temperature (t °C)	$t\text{ }^{\circ}C = (t\text{ }^{\circ}F - 32) / 1.8$
Fahrenheit temperature (t °F)	Kelvin temperature (tk)	$tk = (t\text{ }^{\circ}F + 459.67) / 1.8$
Kelvin temperature (tk)	Celsius temperature (t °C)	$t\text{ }^{\circ}C = tk - 273.15$
Rankine temperature (t °R)	kelvin temperature (tk)	$tk = t\text{ }^{\circ}R / 1.8$

**ATTACHMENT 20D.**

**CO-ORDINATED UNIVERSAL TIME**

1. Co-ordinated Universal Time (UTC) has now replaced Greenwich Mean time (GMT) as the accepted international standard for clock time. It is the basis for civil time in many States and is also the time used in the world-wide time signal broadcasts used in aviation. The use of UTC is recommended by such bodies as the General Conference on Weights and Measures (CGPM), The international Radio Consultative Committee (CCIR) and the World Administration Radio Conference (WARC).
2. The basis for all clock time is the time of apparent rotation of the sun. This is, however, a variable quantity which depends, among other things, on where it is measured on earth. A mean value of this time, based upon measurements in a number of places on the earth, is known as Universal time. A different time scale, based upon the definition of the second, is known as International Atomic Time (TAI). A combination of these two scales results in Co-ordinated Universal Time. This consists of TAI adjusted as necessary by the use of leap seconds to obtain a close approximation (always within 0.5 second) of Universal Time.

**INTENTIONALLY LEFT BLANK**

**ATTACHMENT 20 E.**

**PRESENTATION OF DATE AND TIME IN ALL-NUMERIC FORM**

**1. Introduction**

The International Organization for Standardization (ISO) Standards 2014 and 3307 specify the procedures for writing the date and time in all-numeric form and ICAO will be using these procedures in its documents where appropriate in the future.

**2. Presentation of Date**

Whereas dates are presented in all-numeric form, ISO 2014 specifies that the sequence year-month-day should be used. The elements of the date should be:

- four digits to represent the year, except that the century *digits may be omitted where no possible confusion* could arise from such an omission. There is value in using the century digits during the period of familiarization with the new format to make it clear that the new order of elements is being used;
- two digits to represent the month;
- two digits to represent the day.

Where it is desired to separate the elements for easier visual understanding, only a space or a hyphen should be used as a separator.

As an example, 25 August 1983 may be written as:

19830825 or 830825

or 1983-08-25 or 83-08-25

or 1983 08 25 or 83 08 25.

It should be emphasized that the ISO sequence should only be used where it is intended to use an all-numeric presentation. Presentations using a combination of figures and words may still be used if required (e.g. 25 August 1983).

### 3. Presentation of Time

- 3.1 Where the time of day is to be written in all-numeric form, ISO 3307 specifies that the sequence hours-minutes-seconds should be used.
- 3.2 Hours should be represented by two digits from 00 to 23 in the 24-hour timekeeping system and may be followed either by decimal fractions of an hour or by minutes and seconds. Where decimal fractions of an hour are used, the normal decimal separator should be used followed by the number of digits necessary to provide the required accuracy.
- 3.3 Minutes should likewise be represented by two digits from 00 to 59 followed by either decimal fractions of a minute or by seconds.
- 3.4 Seconds should also be represented by two digits from 00 to 59 and followed by decimal fractions of a second if required.
- 3.5 Where it is necessary to facilitate visual understanding a colon should be used to separate hours and minutes and minutes and seconds. For example, 20 minutes and 18 seconds past 3 o'clock in the afternoon may be written as:
- 52018 or 15:20:18 in hours, minutes and seconds
  - or 1520.3 or 15:20.3 in hours, minutes and decimal fractions of a minute
  - or 15.338 in hours and decimal fractions of an hour

### 4 Combination of Date and Time Groups

This presentation lends itself to a uniform method of writing date and time together where necessary. In such cases, the sequence of elements year-month-day-hour-minute-second should be used. It may be noted that not all the elements need be used in every case – in a typical application, for example, only the elements day-hour minute might be used.